

美國 FPP 使用流量計數據填寫申請表



爲了我們能迅速及準備的處理您的查詢，我們請求，您使用以下表格。請完成填寫相關的內容和傳真您的查詢到營業部(8620)87763873。請複製使用。

聯系入：_____ 客戶：_____ 編號：_____ 日期：_____
 聯系地址：_____ 電話：_____
 公司名稱：_____ 電郵：_____
 油表產品：_____

	正常值	最小值	最大值	
流 速：	_____	_____	_____	加侖/分鍾，公升/分鍾
工 作 壓 力：	_____	_____	_____	PSI BAR kg/cm ² kPa Pa
工 作 溫 度：	_____	_____	_____	攝氏度
粘 溫 性 能：	_____	_____	_____	cst/厘斯

注：以上數據必需填寫，否則不能提供合適的流量計。

以下資料由我司填寫：

Seal material: ·Buna N ·Viton ·Teflon/Kemrez ·Other _____

Registration: ·Mechanical: ·4 Digit=SR-7/SR4-8, unit of calibration : _____

Options: ·PB Solid State Pulser

·5 digit = VR1,unit of calibration: _____

Options: ·VR7671 Solid state Pulser ·VR1871 Reed switch Pulser

·Preset Counter: ·with linkage and mechanical valve

·VR7856,micro switches in X-Proof case

·Ticket Printer: ·accumulative ·zero start

·Electronic : ·Hall Effect pulser ·Reed Switch pulser

·Register or Batch Controller model _____

·Mounted on meter ·remote(add amplifier over 10')

Unit of calibration : _____

Decimals : ·0 ·1 ·2

Power source : ·Battery ·110VAC ·220VAC ·12VDC ·24VDC

Enclosure : ·none/panel mount ·NEMA 3R ·NEMA 4X ·NEMA 7/4X

Accessories :

Inlet side : ·Y-type Strainer ·Basket mesh size: 20 40 80 100

Outlet side : ·Ball valve with linkage,1-stage shut-off ·Brass ·Stainless Steel

·Solenoid valve model : _____

Assembly :

Connections : ·_____ “ NPT BSP female ports

·_____ “150# RF ANSI flange adaptors

·_____ “ _____ adaptors

Direction of Flow : ·Left-to-Right ·Right-to-Left ·Botton-to-top ·Top-to-bottom

E-Z-Batch System : ·Components ·Valves assembled ·All items assembled