



## REX “PG0501” Plastic Gear Lubricant 威斯”PG0501”塑膠齒輪潤滑油

### Description:

REX “PG0501” is a series of white tacky grease with various viscosity and rotating torque. Specially designed for lubrication of plastic gear or any movable part, which requires a light damping effect. It is widely used in toys, electrical appliances, electronic equipments, audio and video equipments manufacturing industries.

### 簡介

威斯 “PG0501” 塑膠齒輪潤滑油 為一系列備有多種黏度及旋扭力之白色黏性油脂，專為塑膠齒輪及需要微緩衝之活動較位潤滑而設，廣泛適用於玩具、家庭電器、電子儀器、影音產品之生產工業。

### Application

- Any plastic gear lubrication requires a light damping effect.
- Plastic / rubber/ metal lubricant.
- Movable joint requires fine tuning or damping.

### 用途

- 所有需要輕度緩衝之塑膠齒輪潤滑油
- 塑膠 / 橡膠 / 金屬潤滑
- 需要定位、微調、緩衝之活動鉸位

### Typical Properties 物理特性

Product 產品	REX PG0501
Appearance 外觀	White tacky grease 白色黏性潤滑脂
NLGI 調度	0
Base Fluid 基礎油	Synthetic / white mineral oil 合成 / 白色礦物油
Operation Temperature 操作溫度	-10°C to 105°C
Dropping point 滴點	160°C
Flash point 閃點	170°C 以上
Special features 特性	new white solid lubricants provide EP-properties and long-term lubrication in areas where contamination has to be avoided 含白色固體原素和抗極壓添加劑，提供長效能潤滑和不污染環境
Toxicity 毒性	Contains no toxic ingredient 不含毒素成份

### Packaging

4Kg/ 5 Kg / 15 Kg

### 包裝

4公斤/ 5 公斤/ 15 公斤

\* All values are typical of standard and may change slightly within the limits giving no influence to the performance of the product.  
上述資料乃標準數據，如變化亦在範圍內，不會影響該產品的功能和表現。

This information is intended as a guide and does not necessarily represent a marketing specification. Data may vary within modest ranges but do not adversely affect the lubricant quality. Modifications reserved.