



REX SG0408 White Multi-Purpose Grease CA100 威斯 SG0408 白色潤滑脂

Description:

REX SG0408 is a white colored and lithium soap mineral grease, containing special solid lubricants enabling a good high and shock capacity as well as a good anti-wear property.

REX SG0408 has a wide range of application and is well suited for plain and anti-friction bearings as well as other grease – lubricated machine elements.

This grease has a good anti-oxidation stability resulting in a long life usage.

Application:

- Power Transistors, General Transistors.
- Diodes, Rectifiers.
- Electronics & Electric Components requiring dissipating heats.

Benefits

- Clean application in white colour
- Prolonged lubrication intervals with special additives
- SGS approvals
- Very good compatibility with most plastic materials
- Wide temperature range: -30°C to +140°C
- Environmentally free in application and non-toxic

簡介

威斯 SG0408 白色潤滑脂作為多用途潤滑脂是白色，鋰基潤滑脂，含有固體原素能提供高負荷、避震及抗磨功能，通用於軸承、導柱、鏈條和齒輪等潤滑。

它有很好的抗氧穩定性，因此有較長潤滑效能的壽命。

用途

- 各類型軸承及齒輪
- 接桿、錠子、導柱等配件
- 適用於食品、啤酒、製衣、紙品、精密配件、家庭電器、電子玩具等工業

優點

- 白色，潔淨使用
- 壽命特長
- 符合SGS認證
- 對大部份塑料兼容性佳
- 工作溫度由-30°C至140°C
- 符合環保及ASTM963-96a 規格，不含毒性物質，防止塑膠老化，適用於多種塑膠如：P.S, PVC, NYLON, ACETOL, P.C., HIGH IMPACT 等

Typical Properties 技術參數

Test Items	SG0408/2	SG0408/1	SG0408/0	Test Method 測試標準
Thickner 填充劑	Li-Soap 鋰皂基	Li-Soap 鋰皂基	Li-Soap 鋰皂基	-
Colour 色澤	White 白色	White 白色	White 白色	-
NLGI No. 調度	2	1	0	-
Worked Penetration (25°C) 針入度	265-295	310-340	400-430	ASTM D 217
Worked Penetration shear stability 100,000 strokes 工作針入度	344	344	344	ASTM D 217

This information is intended as a guide and does not necessarily represent a marketing specification. Data may vary within modest ranges but do not adversely affect the lubricant quality. Modifications reserved.



REX SG0408 White Multi-Purpose Grease CA100
威斯 SG0408 白色潤滑脂

Typical Properties **技術參數**

Test Items	SG0408/2	SG0408/1	SG0408/0	Test Method 測試標準
Base oil viscosity @40°C cSt	80	80	80	ASTM D 446
Water washout @80°C wt%	3.5	3.5	3.5	ASTM D 1264
Anti-rust properties EMCOR rating	0	0	0	DIN 51802
Dropping Point (°C)	195	200	195	ASTM D 2265
Copper Strip Corrosion	1a	1a	1a	KS M 2046
Oil Separation (wt%)	2.5	4.0	2.5	KS M 2050
Oxidation Stability (kg/cm ²)	0.25	0.25	0.25	KS M 2049
4 Ball E.P. (Kg)	310	400	310	ASTM D 2596
4 Ball Wear (mm)	0.59	0.55	0.59	ASTM D 2266
Plastic Compatibility Test	Change lessness 沒變			

Packaging

1KG/5KG/15KGt

包裝

1公斤/5公斤/15公斤

* All values are typical of standard and may change slightly within the limits giving no influence to the performance of the product.
上述資料乃標準資料，如變化亦在範圍內，不會影響該產品的功能和表現。

This information is intended as a guide and does not necessarily represent a marketing specification. Data may vary within modest ranges but do not adversely affect the lubricant quality. Modifications reserved.